





<b>Client</b>	Rugby Joinery	<b>Test date</b>	29-10-98
<b>Test Specimen</b>	Sovereign timber window	<b>Test No</b>	GGF430
<b>Manufactured by</b>	Rugby Joinery	<b>Lab. temp.</b>	21Deg C
<b>Test type</b>	BS7950: 1997 Specification for enhanced security performance of casement & tilt/turn windows for domestic applications.		
<b>Tested by</b>	A.Fowles	<b>Signed</b>	
<b>Checked by</b>	J.Kelly	<b>Signed</b>	
<b>Authorised by</b>	M.Hutton	<b>Signed</b>	
<b>Witnessed by</b>	John Hedgecock (British Woodworking Federation)	<b>Signed</b>	
	Derrick Hatton	Rugby Joinery	
	Andy McShane	Rugby Joinery	
	Stewart Pounder	Hodgson Sealants	

**Specimen details**

<b>Specimen type</b>	Double projecting side hung.	<b>Specimen No</b>	Rugby/9/3 & 4
<b>Material</b>	Softwood	<b>Construction</b>	Jointed

**Fittings**

<b>Lock</b>	Cego Hercules espagnolette gearbox
<b>Shootbolts</b>	Cego Atlas bars with stainless steel screw bushes (two shootbolts and two mushroom pins)
<b>Hinges</b>	Trimfit projection stays with bespoke stainless steel interlocking dog bolts
<b>Fixings</b>	No8 x 30mm screws
<b>Handle</b>	Stanza key locking espagnolette
<b>Glazing</b>	Double glazed toughened units (4-14-4) secured with Hodgson Jumbo Flexistrip 15 x 2.5mm Beads secured with pins and Hodgson Silfix U9 neutral cure silicone

